

TCW216 2xTL-D36W HFS PI

Kod produktu: 58732



Dane techniczne:

- Dimmable **No** [No]
- Full product code **910402607118**
- Full product name **TCW216 2xTL-D36W HFS PI**
- Order code **910402607118**
- Order product name **TCW216 2xTL-D36W HFS PI**
- Pieces per pack **0**
- Bar code on outerbox - EAN3 **8711559103471**
- Packs per outerbox **1**
- Logistic code(s) - 12NC **910402607118**
- Net weight per piece **2.203 kg**
- Product family code **TCW216** [TCW216]
- Number of light sources **2** [2 pcs]
- Lamp family code **TL-D** [MASTER TL-D]
- Lamp power **36 W** [36 W]
- Compensation circuit **No**
- Gear **HFP** [HF Performer]
- Optic type **No**
- Emergency lighting **No**
- Feed-through wiring **No**
- Ingress protection code **IP66** [Dust penetration-protected, jet-proof]
- Input voltage **220-240 V** [220 to 240 V]
- Protection class IEC **CLI** [Safety class I]
- Mech. impact protection code **IK08** [5 J vandal-protected]
- CE mark **CE** [CE mark]
- ENEC mark **ENEC** [ENEC mark]
- Flammability mark **F** [For mounting on normally flammable surfaces]
- Glow-wire test **850/5** [Temperature 850 °C, duration 5 s]
- Light source replaceable **true** [Yes]
- Connection **PI** [Push-in connector 3-pole]
- Driver included **true** [Yes]
- Housing material **PES** [Polyester]
- Ready-to-install **No**
- Electrical circuit protection **No**
- Explosion hazard class **No**
- Country version **No**

- Housing configuration 2 **H2L [2-lamp housing]**
- Mechanical accessories **No**

TCW216 - 2 pcs - MASTER TL-D - 36 W - HF Performer

Pacific TCW216 is a functional dust-, jet-, shock- and vandalproof luminaire, and can accommodate both TL-D and TL5 (16 mm) fluorescent lamps. The cover is fixed to the housing by means of an innovative concept using integrated fixing points to avoid external lockers. There is a choice of different standard versions available. The luminaire can be mounted individually or in-line with easy 'click' installation. Flexibility is ensured with a choice of fixing points and different cable entries. The TCW216 can also be suspended from Philips TTX410 light-line systems.

Features

Dust-, jet-, shock- and vandal-proof

TL-D or TL5 (16 mm) fluorescent lamps

Mounting individually or in lines

Also available in versions for cold stores (-20°C)

Applications

Industry

Indoor workplaces

Parking garages

Cold stores -20°C (XAP)





