

Modena LED 20W 3000K White

Kod produktu: 62781



Dane techniczne:

- Light source power **1x21W**
- Louver/shutter **OPAL**
- Luminaire luminous efficacy **57 lm/W**
- Luminaire luminous flux **1200 lm**
- Color temperature **3000K**
- Weight **1.80 kg**
- Color **White**
- Type of installation **Surface mounted**
- Housing material **Polycarbonate**
- Light source **LED**
- Number of light sources **1**
- Type of equipment **AC**
- Voltage rating **230 V**
- Light source included **Yes**
- Type of LED **LG5630**
- SELV **Yes**
- Igniter/starter **Not required**
- Operating temperature range **-20 ... 40 °**
- Light color **White**
- Color rendering index **80**
- Class of luminaire **I**
- Light distribution **DI**
- Degree of protection (IP) **IP66**
- Class of protection **I**
- Energy class **A+**
- CE **Yes**
- Light source protection **Yes**
- Impact resistance **IK10**

LED version of plafond with high esthetic features and over standard parameters: UV proof, highly resistant to mechanical factors and adverse external conditions. Protection degree IP66, body of high quality material. Emergency module AW 3H. Plafonds available with motion detector, daylight sensor or emergency module.

Materials: white version: base and diffuser made of white UV proof polycarbonate, transparent version: base and diffuser made of transparent UV proof polycarbonate, grey version: grey base and white diffuser made of UV proof

polycarbonate

Installation: ceiling mounted, wall mounted

Power: 230 V

H

110

H - Height / Depth

F - Outer diameter

F

400



