

Finestra LED 11W 4000K MPRM

Kod produktu: 62798



Dane techniczne:

- Light source power **1x11W**
- Luminarie luminous efficacy **900 lm/W**
- Luminarie luminous flux **82 lm**
- Color temperature **4000K**
- Weight **3.40 kg**
- Type of installation **Universal mounting**
- Housing material **Steel sheet**
- Reflector **Mat**
- Diffuser color **None**
- Louver/shutter **MPRM**
- Diffuser material **Prismatic plastic**
- Light source **LED**
- Number of light sources **1**
- Type of equipment **AC**
- Voltage rating **230 V**
- Light source included **Yes**
- SELV **Yes**
- Color **Grey**
- Light color **White**
- Color rendering index **80**
- Class of luminarie **I**
- Light distribution **DI**
- Degree of protection (IP) **IP20**
- Class of protection **I**
- Energy class **A+**
- CE **Yes**
- Light source protection **Yes**

Energy-saving decorative lighting luminaire of modern and elegant shape equipped with LED light source from renowned producers. Finestra by universal form and type of assembly is suitable for public spaces, conference rooms, offices, communications, halls, stairways. The first-class AC power supply of renowned brands achieves $\cos \phi > 0,95$. This luminaire perfectly complements to the rest of the Finestra series of luminaires.

Materials: powder painted steel housing (standard color: grey), microprismatic MPRM or prismatic PRM diffuser

Installation: ceiling mounted, suspenden, wall mounted

Accessories: simple and electric suspension

Power: 230 V

	L	W	H
PX0906263 11W	307	307	68
PX0906268 11W	307	307	68
PX0906283 24W	407	407	65
PX0906288 24W	407	407	65

L - Length

W - Width

H - Height / Depth



