

Greenlight LED 9W 4000K 115° 50X100

Kod produktu: 62836



Dane techniczne:

- Light source power **1x9W**
- Info **115° 50X100**
- Luminaire luminous efficacy **54 lm/W**
- Luminaire luminous flux **490 lm**
- Color temperature **4000K**
- Weight **1.10 kg**
- Type of installation **Pole mounted**
- Housing material **Aluminum**
- Reflector **High gloss**
- Diffuser color **None**
- Diffuser material **Opal glass**
- Light source **LED**
- Number of light sources **1**
- Type of equipment **Not required**
- Voltage rating **230 V**
- Light source included **Yes**
- Type of LED **VS**
- SELV **Yes**
- Light source power **9W**
- Luminaire power **9 W**
- Color **Anthracite**
- Operating temperature range **-20 ... 40 °**
- Light color **White**
- Color rendering index **80**
- Class of luminaire **I**
- Light distribution **DI**
- Degree of protection (IP) **IP65**
- Class of protection **I**
- Energy class **A**
- CE **Yes**
- Light source protection **Yes**
- Impact resistance **IK08**

Luminaire designed for LED light sources in the form of a rectangle pillar. Various colors, dimensions and slopes available as a standard. Perfect solution for discreet lighting of buildings surroundings, paths and gardens.

Materials: housing made of aluminum profile painted with a paint resistant to external conditions (standard color: graphite, other colours on request, frosted glass)

Installation: for the ground

Power: 230 V

	L	W	H
PX4059001 9W	60	50	170
PX4059008 9W	60	50	170
PX4059015 9W	100	50	120
PX4059022 9W	100	50	120
PX4059029 9W	100	50	170
PX4059036 9W	100	50	170

L - Length

W - Width

H - Height / Depth



