

# Owa Road At 3j Led3 9003

Kod produktu: 68646



Dane techniczne:

- Work Mode **maintained**
- emergency work time **3h**

Features:

Owa LED, equipped with LED light source, is a recessed highly efficient luminaire designed for emergency lighting. Its main task is to illuminate emergency escape routes, emergency escape exits and rooms in public facilities, work places, etc. It is compatible with all emergency lighting systems offered by Hybryd. Different versions available.

Technical data:

| CATEGORY                                | VALUE                                                                                      |
|-----------------------------------------|--------------------------------------------------------------------------------------------|
| Power supply                            | 230V 50Hz                                                                                  |
| Power consumption                       | <7VA                                                                                       |
| Protection class                        | I                                                                                          |
| Protection degree                       | IP 20, IP44 ( wersja oprawy IP44 na specjalne zamówienie)                                  |
| Light source                            | Modul LED (unchangeable light source)                                                      |
| Minimal luminous flux                   | 250 lm                                                                                     |
| Light source power                      | 3W                                                                                         |
| Light source lifespan                   | >50 000h                                                                                   |
| Accumulator type (according to version) | NI-MH HT, Ni-Cd HT                                                                         |
| Accumulator voltage                     | 4,8V                                                                                       |
| Accumulator capacity                    | 1,5Ah, 2,5Ah, 4,0Ah                                                                        |
| Recharging type                         | 24h                                                                                        |
| Emergency work time                     | 1h, 2h, 3h                                                                                 |
| Ambient temperature                     | +10°C ÷ +40°C                                                                              |
| Connector                               | 4 x 0,5 +2,5 mm <sup>2</sup> (maintained)<br>3 x 0,5 +2,5 mm <sup>2</sup> (non-maintained) |

Casing:

Body material: extruded aluminium

Casing colour: white, black, silver, different colours available