

# Profil At J Led W12

Kod produktu: 68704



## Dane techniczne:

- Work Mode **maintained**
- emergency work time **3h**

## Features:

Profil luminaire is supposed to indicate emergency escape routes and emergency exits with suitable pictograms. Profil can be adopted in public facilities or in workplaces and it is compatible with all emergency lighting systems offered by Hybryd.

## Technical data:

| CATEGORY / LIGHT SOURCE | LED                                                                                          |
|-------------------------|----------------------------------------------------------------------------------------------|
| Power supply            | 230V 50Hz                                                                                    |
| Power consumption       | <4VA                                                                                         |
| Protection class        | I                                                                                            |
| Protection degree       | IP 40                                                                                        |
| Light source            | White LED                                                                                    |
| Accumulator type        | Ni-MH HT                                                                                     |
| Recharging type         | 24h                                                                                          |
| Emergency work time     | 3h                                                                                           |
| Ambient temperature     | +10°C ÷ +40°C                                                                                |
| Connector               | 4 x 0,5 ÷ 2,5 mm <sup>2</sup> (maintained)<br>3 x 0,5 ÷ 2,5 mm <sup>2</sup> (non-maintained) |

## Casing:

- body material - aluminium
- colour: silver (oxidized aluminium),  
other RAL colour available
- lamp cover: flat transparent (plexiglass with pictogram)

**PICTOGRAMS:**



**Mounting types:**

