

CARO 2 LED bracket ED 230V/50Hz 12x1W red IP65 22st. grey

Kod produktu: 70916



Dane techniczne:

- Lumen LED[lm] **540**
- Luminaire power [W] **17**
- Power LED[W] **2x6**
- Efficacy[lm/W] **24**
- Lumen luminaire[lm] **400**
- Mounting **surface mounted**
- Body **high pressure die-cast aluminum**
- Includes light source **yes**
- Power supply efficiency **>71%**
- Electrical connection **3x2,5 mm² wire**
- Warranty **3 years + 2 years after project registration**
- Application **facades, hotels, shopping centers, restaurants, museums**
- Lifetime **50 000 h**

Wall luminaires being perfect solution for facade illumination - different beam angles and LED colors possible.

Code	Dimensions [mm] L W H D	Dimensions de découpe [mm] H D	Pallet quantity	Quantity in package	Net weight[kg]
140132.5L011 .604	270 150 200 1 80 60 00	112	1	3,8	
140132.5L011 .607	270 150 200 1 80 60 00	112	1	3,8	
140132.5L011 .608	270 150 200 1 80 60 00	112	1	3,8	
140132.5L012 .604	270 150 200 1 80 60 00	112	1	3,8	
140132.5L012 .607	270 150 200 1 80 60 00	112	1	3,8	
140132.5L012 .608	270 150 200 1 80 60 00	112	1	3,8	
140132.5L013 .604	270 150 200 1 80 60 00	112	1	3,8	

Code	Dimensions [mm] L W H D	Dimensions de découpe [mm] H D	Pallet quantity	Quantity in package	Net weight[kg]
140132.5L013 .607	270 150 200 1 80 60 00	112	1	3,8	
140132.5L013 .608	270 150 200 1 80 60 00	112	1	3,8	
140132.5L014 .604	270 150 200 1 80 60 00	112	1	3,8	
140132.5L014 .607	270 150 200 1 80 60 00	112	1	3,8	
140132.5L014 .608	270 150 200 1 80 60 00	112	1	3,8	
140132.5L015 .604	270 150 200 1 80 60 00	112	1	3,8	
140132.5L015 .607	270 150 200 1 80 60 00	112	1	3,8	
140132.5L015 .608	270 150 200 1 80 60 00	112	1	3,8	
140132.5L016 .604	270 150 200 1 80 60 00	112	1	3,8	
140132.5L016 .607	270 150 200 1 80 60 00	112	1	3,8	
140132.5L016 .608	270 150 200 1 80 60 00	112	1	3,8	

